

JS36

闭式双点压力机 STRAIGHT-SIDE TWO POINT PRESS

技术参数Specifications		单位	JS36-250	JS36-300	JS36-300A	JS36-400	JS36-400A	JS36-500	JS36-500A	JS36-630	JS36-630A	JS36-800	JS36-1000	JS36-1250	JS36-1600	JS36-1600A
公称力Nominal Capacity		KN	2500	3000	3000	4000	4000	5000	5000	6300	6300	8000	10000	12500	16000	16000
公称力行程Nominal pressure stroke		mm	13	13	13	13	13	13	13	13	13	13	13	13	13	20
滑块行程长度Slide Stroke		mm	400	400	500	400	500	400	500	500	250	500	500	600	500	650
滑块行程次数Slide Strokes Per Minute		spm	16	16	18	16	18	16	12-16	14	20	10	10	12	10	9-16
最大装模高度Max Die Set Height		mm	650	720	1050	770	1050	650	1000	1100	850	990	1000	1300	950	1200
装模高度调节量Die Set Height Adjustment		mm	315	400	400	400	400	400	500	500	250	400	400	500	400	700
工作台面尺寸(前后×左右)Bolster Size(LR×FB)		mm	1300×2600	1600×2800	1600×2800	1600×2800	1600×3000	1600×2800	1600×3000	1800×3800	1800×3500	1800×3640	2000×4000	2000×4000	2000×5000	1600×4000
滑块底面尺寸(前后×左右)Slide Bottom Size(LR×FB)		mm	1300×2600	1600×2800	1600×2800	1600×2800	1600×3000	1600×2800	1600×3000	1800×3800	1800×3500	1800×3640	2000×4000	2000×4000	2000×5000	1600×4000
滑块打料杆	型式Structure		刚性	刚性	刚性	刚性	刚性	刚性	气动	刚性	刚性	刚性	刚性	刚性	气动	气动
Side knockout rod	打料力Knockout pressure	KN	100	150	150	150	150	150	100	150	150	150	150	150	100	100
气垫	压紧力/顶出力Clamping pressure/Withdraw	KN	510/510	600/600	600/600	600/600	600/600	600/600	800/800	1000/1000	120/120	1000/1000	1200/1200	1500/1500	1500/1500	1500/1500
Cushion	数量Quantity		单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠	单顶冠
	行程Stroke	mm	200	200	0-250	200	0-250	200	200	250	150	250	250	250	250	0-250
电气控制形式			PLC													
移动台移动方式Moving working table method																
主电机功率Motor Power	KW		30	37	37	45	55	55	75	90	90	90	110	132	132	250
压力机地面以上高度Height press above floor	mm		6960	7000	7240	7000	7450	7400	7800	8000	7380	8500	9000	9900	9800	9500
压力机外形尺寸(前后×左右)Overall Dimensions(FB×LR)	mm		4200×4760	4000×5100	4730×4550	4000×5100	4730×4550	4000×5100	4800×5600	4370×6200	4050×5950	4600×6800	5600×8500	5300×7500	5600×8500	6200×7500
压力机整机重量Weight	Kg		75000	90000	130000	104000	140000	142000	170000	180000	156000	210000	255000	320000	480000	400000

(可根据用户要求定制产品) 本样本内容如有变更, 恕不另行通知。The contents are subject to change without prior notice.

性能特点:

- ☀ 大件采用有限元分析
- ☀ 采用通用化、标准化、模块化设计
- ☀ 采用专用的离合器制动器
- ☀ 具有高性能、高精度、高稳定性
- ☀ 采用重载润滑系统
- ☀ 采用超长导轨导向
- ☀ 采用进口液压过载保护装置
- ☀ Solidwork优化设计传动系统和外观

该系列机床为通用性较广的冲压设备, 可以进行冲裁、成形、弯曲、浅拉伸、冷冲压等加工工序, 对冲制各种薄板成形零件更为合适。该系列广泛应用于汽车、机车车辆、船舶、航空等行业。该系列机床可带有多种形式的移动工作台, 并用PLC控制。

JS36

STRAIGHT-SIDE
TWP POINT PRESS



FEATURES:

- ⊗ Adopt finite element analysis for major parts;
- ⊗ Adopt generalized, standard and modular design;
- ⊗ Adopt special clutch brake;
- ⊗ Feature high performance, high accuracy and stability;
- ⊗ Adopt heavy-duty lubrication system;
- ⊗ Adopt ultra-long guide rail for guidance;
- ⊗ Adopt imported hydraulic overload protection device ;
- ⊗ Solidwork optimized design of driving system and appearance.

